

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors **Rotary Compressor:** Fixed Speed

1	MODEL DATA - FOR COMPRE			
1	······································			
	Model Number: G7-125TM	Date:	6/29/2020	
2	X Air-cooled Water-cooled	Type:	Screw	
		# of Stages:	1	
3*	Rated Capacity at Full Load Operating Pressure a, e	40	acfm ^{a,e}	
4	Full Load Operating Pressure ^b 125		psig ^b	
5	Maximum Full Flow Operating Pressure ^c	ating Pressure ^c 132		
6	Drive Motor Nominal Rating	10	hp	
7	Drive Motor Nominal Efficiency	90.3	percent	
8	Fan Motor Nominal Rating (if applicable)	0.4	hp	
9	Fan Motor Nominal Efficiency	N/A	percent	
10*	Total Package Input Power at Zero Flow ^e	4.7	kW ^e	
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d	10.8	kW^d	
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e	27.0	kW/100 cfm	
13	Isentropic Efficiency	55.63	Percent	

a party Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES: a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured for this data sheet. Member

c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.



ROT 030.1

 a. Total package input power at other than reported operating points will vary with control strategy.
e. Tolerance is specified in ISO 1217, Annex C, as shown in table below: NOTE: The terms "power" and "energy" are synonymous for purposes of this document. 1 Mal.

Institute	Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
	<u>m³ / min</u>	<u>ft3 / min</u>	%	%	
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	
	Above 15	Above 529.7	+/- 4	+/- 5	

2/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data