

COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors **Rotary Compressor:** Fixed Speed

1	Manufacturer: Atlas Copco		
	Model Number: G7-150TM	Date:	6/29/2020
2	X Air-cooled Water-cooled	Type:	Screw
		# of Stages:	1
3*	Rated Capacity at Full Load Operating Pressure a, e	35	acfm ^{a,e}
4	Full Load Operating Pressure ^b	150	psig ^b
5	Maximum Full Flow Operating Pressure ^c	157	psig ^c
6	Drive Motor Nominal Rating	10	hp
7	Drive Motor Nominal Efficiency	90.3	percent
8	Fan Motor Nominal Rating (if applicable)	0.4	hp
9	Fan Motor Nominal Efficiency	N/A	percent
10*	Total Package Input Power at Zero Flow ^e	4.3	kW ^e
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d	10.5	kW^d
12*	Specific Package Input Power at Rated Capacity and Full Load Operating Pressure ^e	30.0	kW/100 cfm
13	Isentropic Efficiency	55.14	Percent

Program, these items are verified by the third party adm CAGI Perfor Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES: a. Measured at the discharge terminal point of the compressor package in accordance with

ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.

	150 1217, Annex C, ACFW is actual cubic feet per initiate at infet conditions.
b.	The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured
	for this data sheet.
c.	Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the

c. 1 l flow, us maximum pressure attainable before capacity control begins. May require additional power. d. Total package input power at other than reported operating points will vary with control strategy.
e. Tolerance is specified in ISO 1217, Annex C, as shown in table below: NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



ROT 030.1

Member

Volume Flow Rate Specific Energy No Load / Zero Volume Flow Rate Flow Power at specified conditions Consumption m^3 / min <u>ft3 / min</u> % % Below 0.5 Below 17.6 +/- 7 +/- 8 0.5 to 1.5 17.6 to 53 +/- 6 +/- 7 +/- 10% 1.5 to 15 53 to 529.7 +/- 5 +/- 6 Above 15 Above 529.7 +/- 4 +/- 5

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data